

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) An electron gun assembly resistor comprising:
an insulating substrate;
a plurality of electrode elements formed on the insulating substrate and looking like islands;
a resistor element connecting the electrode elements together and providing a predetermined resistance value; and
a plurality of metallic terminals which include flanges in contact with the electrode elements, and which are connected to the electrode elements, the electron gun assembly resistor satisfying

$$\cancel{L1 \leq L2} \quad \underline{L1 < L2},$$

where L1 is an outer dimension of at least one of the electrode elements, and L2 is an outer dimension of the flange of the metallic terminal that is connected to the electrode element whose outer dimensions is L1.

2. (Original) An electron gun assembly resistor according to claim 1, wherein the flanges are located outward of outer peripheries of the electrode elements.
3. (Original) An electron gun assembly resistor according to claim 1, wherein the flanges include tip ends that are curved to cover the electrode elements.
4. (Currently Amended) A cathode ray tube apparatus comprising:
a face panel;
a funnel integrally connected to the face panel;

a phosphor screen formed on an inner surface of the face panel;
an electron gun assembly arranged in a neck of the funnel, configured to emit electron beams toward the phosphor screen, and including a plurality of grid electrodes; and
an electron gun assembly resistor arranged in the neck and juxtaposed to the electron gun assembly, the electron gun assembly resistor dividing a voltage based on a predetermined voltage division ratio and permitting a divided voltage to be applied to at least one of the grid electrodes,
the electrode gun assembly resistor comprising:
an insulating substrate;
a plurality of electrode elements formed on the insulating substrate and looking like islands;
a resistor element connecting the electrode elements together and providing a predetermined resistance value; and
a plurality of metallic terminals which include flanges in contact with the electrode elements, and which are connected to the electrode elements,
the electron gun assembly resistor satisfying

$$L1 \leq L2 \quad \underline{L1 < L2},$$

where L1 is an outer dimension of at least one of the electrode elements, and L2 is an outer dimension of the flange of the metallic terminal that is connected to the electrode element whose outer dimension is L1.

5. (Currently Amended) A cathode ray tube assembly according to claim 4, wherein the flanges are located outward of outer peripheries of the electrode elements.

6. (Currently Amended) ~~An electron gun assembly resistor~~ A cathode ray tube assembly according to claim 4, wherein the flanges include tip ends that are curved to cover the electrode elements.

7. (Original) An electron gun assembly resistor configured to divide a voltage based on a predetermined voltage division ratio and to permit a divided voltage to be applied to an electrode of an electron gun assembly, the electron gun assembly resistor comprising:

- an insulating substrate;
- a plurality of electrode elements formed on the insulating substrate;
- a resistor element connecting the electrode elements together and providing a predetermined resistance value;
- an insulating coating layer which covers the resistor element; and
- a plurality of metallic terminals connected to the electrode elements, respectively, the metallic terminals being arranged without exposing the electrode elements, the insulating coating layer being coated on peripheries of the metallic terminals and being located away from the electrode elements.

8. (Original) An electron gun assembly resistor according to claim 7, wherein regions where the insulating coating layer covers the peripheries of the electrode elements are regions where the insulating substrate has surface portions that are electrically charged to have a potential higher than that of the metallic terminals.

9. (Original) An electron gun assembly resistor according to claim 7, wherein the metallic terminals include flanges which are in contact with the electrode elements, and the flanges have an outer dimension greater than that of the electrode elements and include

Application Serial No.: 10/830,036
Reply to Office Action dated August 9, 2005

portions located outward of the peripheries of the electrode elements.

10. (Original) An electron gun assembly resistor according to claim 9, wherein the insulating coating layer covers the peripheries of the flanges of the metallic terminals without exposing the insulating substrate.